
BRACKETT



BRACKETT 108527 HOT MELT ADHESIVE

SPECIALLY FORMULATED FOR ALL AUTOMATIC PADDING APPLICATIONS

PRODUCT TYPE: Specially formulated Hot Melt adhesive consisting of 100% thermoplastic resin.

APPLICATIONS: Developed exclusively as a padding adhesive where the finished product consists of very difficult to bond materials requiring an adhesive with extreme bonding capabilities. This is our most aggressive adhesive.

FEATURES*: Made for *extra* hold, it is a clear, flexible, high-performance hot melt adhesive with a long pot life and a good balance of adhesion, heat stability and hot tack. However, it requires a bit longer set time and **does not** feature the low-smoke/low-odor characteristic of other Brackett Padding adhesives. This glue can be combined with our other glues to achieve a custom blend with properties of both glues.

APPLICATION EQUIPMENT: Brackett 108527 is formulated for use in any padding machine using an open wheel type applicator such as the Brackett PadMaster 2000 or the Brackett Circular Padder.

FDA STATUS: Ingredients comply with regulations for use in food packaging adhesives as per FDA regulation 175.105

COLOR:.....Translucent Pale Amber
IDEAL APPLICATION TEMP.:..... 335 °F
TEMPERATURE RANGE:..... 325-340 °F
RING & BALL SOFTENING POINT: :..... 160-162 °F
SPEED OF SET:.....Medium
HEAT STABILITY:..... Good to 100 Hours
VISCOSITY:..... 2000 cps @ 350 °F

CLEANUP SOLVENT: Brackett #108503 Master Purge, wax or other hot melt cleaners.

STORAGE CONDITIONS: Store at room temperature. Rotate stock using oldest material first. Shelf life is 12 months.

* **Note:** The above statements are suggestions only.....final testing for suitability remains the responsibility of the user. *These products contain no chemicals listed under California proposition 65.*

BRACKETT, INC., P.O Box 19306, Bld. 451 J Street, Forbes Field, Topeka, KS 66619 • USA
E-Mail brackett@brackett-inc.com • Web www.brackett-inc.com
Phone 800-255-3506 • 785-862-2205 • Fax 785-862-1127