

BRACKETT

Utility Stripping / Taping Machines

PRODUCT SPECIFICATION SHEET

Manual infeed machine:

Work Width -- Side to Side of page
Minimum: 3.00 inches (76.2 mm)
Maximum: 15.00 inches (381.0 mm)
Work Length -- Top to bottom of page
Minimum: 5.50 inches (139.7 mm)
Maximum: 23.00 inches (584.2 mm)
Work Thickness
Minimum: .03125 inches (.793 mm)
Maximum: 1.25 inches (31.75 mm)

Hopper Spacer infeed machine:

Work Width -- Side to Side of page
Minimum: 3.00 inches (76.2 mm)
Maximum: 14.00 inches (355.6 mm)
Work Length -- Top to bottom of page
Minimum: 7.00 inches (177.8 mm)
Maximum: 17.00 inches (431.8 mm)
Work Thickness
Minimum: .125 inches (3.18 mm)
Maximum: 1.25 inches (31.75 mm)

Tape Specifications --

Roll core diameter minimum: .500 inches (12.7 mm)
Maximum roll diameter: 19.00 inches (482.6 mm)
Maximum roll width: 3.75 inches (95.25 mm)
Tape wrap side maximum: 1.25 inches (31.75 mm)

Stripping tape glue pot --

Hot animal, cold glue, water.
Optional hot melt stripping pot mounted on universal stand.

Machine speed --

Minimum: 20 feet per minute (6.096 meters)
Maximum: 81 feet per minute (24.69 meters)

Electrical requirements --

Standard: 120 Volt, Single phase, 60 Hertz, 20 Amps
Options: Other electrical available as option at time of manufacture

Weight -- *Basic machine:* 560 lbs. (254 kg)

Shipping crate -- (Approximate)

Basic machine: Inches = 76 L x W x 55 H
Centimeters = 193 L x 94 W x 140 H

Brackett Inc.

P.O. Box 19306

Topeka, KS 66619

(800)-255-3506 (785)-862-2205

FAX (785)-862-1127

E-Mail: sales@brackett-inc.com

Internet: www.brackett-inc.com