

Brackett Inc.**X-30 System**

Machine Specifications	X-30 Padding and Pressure Sensitive Taping Machine
Work Length Min	7" (18cm)
Work Length Max..	44" (111cm)
Work Thickness Min.	3/16" (.47cm)
Work Thickness Max.	1 1/2" (3.8cm)
Work Height Min.	3" (7.6cm)
Work Height Max.	36" (91.4cm)
Tape Roll Dia. Max	18" (45.7cm)
Roll Core Dia.	1/2" (12.7cm)
Roll Width Max.	3" (7.6cm)
Max Wrap Around Work	1" (2.54cm)
Machine Speed - Max.	125 FPM
Electrical Requirements	40 amps at 230V 50/60Hz, 1P
Tape Knife Cylinder Air Requirements (VTOP-11)	5 CFM at 80 PSI
Weight -Basic Machine	
Weight - Batcher Del.	
Main Drive Motor	3 HP Var. Speed
Rougher/Grinder Motor	3 HP, 3600 RPM
Notching Depth	1/16" (.158cm)
Work Padding Pot	
Type of Adhesive	Hot Melt
Glue Temp. Range F° (C°)	200-360 (93-182)
Pot Capacity	8lbs
Padding Pot Pre-Melt Unit	
Type of Adhesive	Hot Melt Pre-Melter
Pot Temperature Range F° (C°)	Preset 340F (171C)
Pot Capacity	5 Gal. (19Liters)
Stripping Tape Glue Pot	N/A
Type of Adhesive	Hot Melt Stripping
Pot Temperature Range F°/C°	200-360F (98-182C)
Pot Capacity	8lbs (144CL)

BRACKETT, INC.

PO Box 19306

Topeka, KS 66619 USA

(800) 255-3506 (785) 862-2205

Fax: (785) 862-1127

E-Mail: sales@brackett-inc.com

<http://www.brackett-inc.com>